

4C 4D



4C

MODEL CODE

(Approved code)

4C 6GP (6GPK)

4D 6GV (6GVK)

MODELS AVAILABLE

Tiller Handle

4C MH

4D MH

Dry weight

21 – 22 kg

SPECIFICATIONS

Performance	4C	4D
Max. prop shaft output	2.9 kW (4 ps)	
Full throttle operating range	4500 – 5500 r/min	
Idling speed	1100 – 1200 r/min	
Fuel consumption	2.8 L/h @5500 r/min	

Engine

Engine type	1-cylinder
Displacement	103 cm ³
Bore × stroke	54.0 × 45.0 mm
Compression ratio	6.5 : 1
Starting enrichment	Manual choke
Scavenging	Cross flow
Fuel induction system	1 carburetor
Lubrication system	Pre-mixed fuel and oil
Oil - fuel mixing ratio	50 : 1 (EUR, CRB 100 : 1)
Engine oil capacity	—
Built-in fuel tank	2.8 L
Ignition system	CDI
Ignition timing	BTDC 5.0 – 28.0 deg.
Spark plug	B7HS
Alternator	60 W (optional)
Cooling system	Raw-water, thermostatically controlled
Exhaust system	Under water

Bracket / Drive

Trim	5 positions
Shallow water drive	3 positions
Steering angle	360 deg.
Gear shift	F-N-R
Gear ratio	2.08 (27/13)
Gear oil capacity	0.100 L
Propeller fitting	Spline
Propeller rotation	Clockwise
Shaft length	S, L (4D: S)
Engine transom height	S : 444 mm (17.5 in), L : 571 mm (22.5 in)

FEATURE TABLE

CATEGORY	FEATURE ITEM	4C	4D
		MH	MH
Security	Start in gear protection	●	●
	Engine stop switch lanyard	●	●
	Over rev. limiter	—	—
	Overheat warning	—	—
Corrosion prevention	Stainless steel water pump housing	●	●
	Chrome plated water pump housing	—	—
	Stainless steel water tube	—	—
	Single large anode	●	●
Power unit	Corrosion free resin propeller	—	—
	Carburetor	●	●
	Gasoline [Regular]	●	●
Convenience	Carrying handle	—	—
	Built-in fuel tank	●	—
	2-way fuel supply system	●	—
	360 deg. full pivot steering	●	●
	Shallow water drive	●	●

— : N/A (Not available)

OPTIONAL ACCESSORY GUIDE

OPTIONAL ACCESSORY	4C	4D
	MH	MH
Lighting coil	●	●
Portable fuel tank	●	●
Spark plug	●	●
PROPELLER	4C	4D
	MH	MH
Standard propeller	—	—
• Traditional propeller	—	—
• Weedless propeller	BA	BA
CONSUMES	4C	4D
	MH	MH
Yamalube 2, 2M	●	●
Yamalube gear oil (GL4)	●	●
Yamaha grease A	●	●
Yamaha grease D	●	●